



Global[®] LP 1970 Special series - Postbed shoe machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 3500 spm

Stitch type
301

Number of needles
1 or 2

Stitch length
up to 5 mm

Feed type
**reversible needle feed
top driven roller and
wheel feed**

Needle type
134

Bed type
postbed

Roller presser
standard 35 mm ø

Hook
regular hook

LP 1971-725 - High speed, single needle left hand postbed machine with top driven roller presser and double intermittent wheel and needle feed. Machine is equipped with lower electric edge cutter and regular hook.

LP 1971-725 AUT - Same as above, but with electric thread trimmer, presser foot lift and automatic back tack.

LP 1972-725 - Same as LP 1971-725, but with two needles.

LP 1972-725 AUT - Same as LP 1971-725 AUT, but with two needles.

LP 1971-745 - High speed, single needle right hand postbed machine with top driven roller presser and double intermittent wheel and needle feed. Machine is equipped with lower electric edge cutter and regular hook.

LP 1971-745 AUT - Same as above, but with electric thread trimmer, presser foot lift and automatic back tack.

LP 1971-7 - High speed, single needle left hand postbed machine with top driven roller presser and double intermittent wheel and needle feed. Machine is equipped with motor driven oblique knife and standard hook.

LP 1971-7 AUT - Same as above, but with electric thread trimmer, presser foot lift and automatic back tack.

MÁQUINAS DE CALZADO CON RETROCESO

LP 1971-725 - Máquina de alta velocidad, con el poste a la izquierda. Arrastre por diente circular, aguja y ruleta accionada. La máquina esta equipada con recorte eléctrico y garfio normal.

LP 1971-725 AUT - Mismas características que la anterior, pero con corta-hilos, remate y alza-prensatelas eléctrico.

LP 1972-725 - Mismas características que la LP 1971-725, pero con 2 agujas.

LP 1972-725 AUT - Mismas características que la LP 1971-725 AUT, pero con 2 agujas.

LP 1971-745 - Máquina de alta velocidad, con el poste a la derecha. Arrastre por diente circular, aguja y ruleta accionada. La máquina esta equipada con recorte eléctrico y garfio normal.

LP 1971-745 AUT - Mismas características que la anterior, pero con corta-hilos, remate y alza-prensatelas eléctrico.

LP 1971-7 - Máquina de alta velocidad, con el poste a la izquierda. Arrastre por diente circular, aguja y ruleta accionada. La máquina esta equipada con recorte obliquo eléctrico y garfio normal.

LP 1971-7 AUT - Mismas características que la anterior, pero con corta-hilos, remate y alza-prensatelas eléctrico.

MACHINE CHAUSSURE AVEC MARCHE ARRIÈRE

LP 1971-725 - Machine pilier à gauche 1 aiguille - haute vitesse - entraînement par pied à roulette entraîné, aiguille et griffe circulaire à mouvement intermittent. Equipée avec couteau raseur inférieur et crochet standard.

LP 1971-725 AUT - Identique à la précédente, mais équipée avec coupe-fils électrique, relevage de pied et arrêts automatiques.

LP 1972-725 - Identique à la LP 1971-725, mais avec deux aiguilles.

LP 1972-725 AUT - Identique à la LP 1971-725 AUT, mais avec deux aiguilles.

LP 1971-745 - Machine pilier à droite 1 aiguille - haute vitesse - entraînement par pied à roulette entraîné, aiguille et griffe circulaire à mouvement intermittent. Equipée avec couteau raseur inférieur et crochet standard.

LP 1971-745 AUT - Identique à la précédente, mais équipée avec coupe-fils électrique, relevage de pied et arrêts automatiques.

LP 1971-7 - Machine pilier à gauche 1 aiguille - haute vitesse - entraînement par pied à roulette, aiguille et griffe circulaire à mouvement intermittent. Equipée avec couteau raseur commandé par moteur indépendant et crochet standard.

LP 1971-7 AUT - Identique à la précédente, mais équipée avec coupe-fils électrique, relevage de pied et arrêts automatiques.

Global LP 1970 Series

Single and double needle postbed machines for the shoe industry. These unique machines are equipped with automatic or manual back tack on the lower and upper feed as well as on the needle feed. These machines are easy to maintain and very flexible to operate.



LP 1970 Special series - Standard equipped with manual reverse

Special features:

- Unique lubrication system
- Automatic and / or manual back tack
- 8 - 11 mm short cut of thread trimmer
- Max. thickness of sewing goods: 8 mm
- Max. foot lift: 12,5 mm
- Needle bar stroke: 40 mm
- All automatic functions by solenoids
- Built-in safety clutch
- Simple to maintain
- All machines are equipped with 35 mm Ø top roller
- All important adjustments via handwheel
- All machines are equipped with vertical standard hook(s)

Specifications for the basic LP 1970 Special series

LP Machines	1971-725	1971 - 725 AUT	1972-725	1972-725 AUT	1971-745	1971-745 AUT	1971-7	1971-7 AUT
number of needles	1	1	2	2	1	1	1	1
needle size	80 - 110	80 - 110	80-110	80-110	80 - 110	80-110	80-110	80-110
needle gauge	-	-	1.6	1.6	-	-	-	-
needle hole width (mm)	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
electric solenoid reverse	-	•	-	•	-	•	-	•
electric solenoid presser foot lift	-	•	-	•	-	•	-	•
thread trimming device	-	•	-	•	-	•	-	•
electric oblique knife	-	-	-	-	-	-	•	•
electric under fabric trimming	•	•	•	•	•	•	-	-
max. stitch length mm	5	7	5	7	5	7	5	7
lower feeding wheel teeth (mm)	0.4	1.2	0.4	1.2	0.4	1.2	0.4	1.2
cutting width	0.8 - 1.2	0.8 - 1.2	0.8 - 1.2	0.8 - 1.2	0.8 - 1.2	0.8 - 1.2	0.8 - 1.2	0.8 - 1.2
machine speed* (spm)	3000	1600	3000	1600	2500	1200	2500	1200
post model ■ left ■ right	■	■	■	■	■	■	■	■

Extra available subclasses

LP 197...Subclass	1971 L	1971 M	1972 L
Needle size	60 - 80	110 - 140	60 - 80
Needle hole width (mm)	1.2	2.0	1.2
Needle gauge (mm)	-	-	1.2
Max. Stitch length (mm)	3	5	5
Lower feeding wheel teeth (mm)	0.4	0.6	0.4
Machine speed*	3500	2000	3500

L = light material / M = medium / heavy material



LP 1971-7



LP 1971-725-AUT

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:
 1 machine model
 2 part numbers