



GC20606



**ONE AND TWO NEEDLE
COMPOUND FEED LOCKSTITCH SEWING MACHINE**
**EIN- UND ZWEINADEL
3-FACH-TRANSPORT-STREPPSTICH-NÄHMASCHINE**

TYPICAL

GC20606

**ONE AND TWO NEEDLE
COMPOUND FEED LOCKSTITCH SEWING MACHINE
EIN- UND ZWEINADEL
3-FACH-TRANSPORT DOPPELSTIPPSTICH-NÄHMASCHINE**

Technical Data

- Stitch type 301
- Vertical hook
- Max. sewing speed 1,800 spm.
- Max. stitch length 9 mm
- Max. fabric clearance 13 mm with knee lever
- Balance wheel 93 mm eff. Dia.

Clearance under the arm

- 250x100 mm

Automatic oil pump lubrication system

Models

- **GC20606-1**
1 needle machine
- **GC20606-1D2**
1 needle machine with thread cutter and back tack
- **GC20606**
2 needle machine
- **GC20606-D2**
2 needle machine with thread cutter and back tack

Carton dimensions and gross weights for sewing head

- 72x27x67 cm, 47 kg

Technische Daten

- Stichtyp 301
- Vertikalgreifer
- Max. Nähgeschwindigkeit 1.800 Stiche / Minute
- Max. Stichlänge 9 mm
- Max. Durchgang unter dem Nähfuß 13 mm mit Kniehebel
- Handrad-Durchmesser effektiv 93 mm

Durchgangsraum im Nähmaschinenarm

- 250x100 mm

Automatisches Druckumlauf-Schmiersystem

Ausführungen

- **GC20606-1**
1-Nadelmaschine
- **GC20606-1D2**
1-Nadelmaschine mit Fadenabschneider und Verriegelung
- **GC20606**
2-Nadelmaschine
- **GC20606-D2**
2-Nadelmaschine mit Fadenabschneider und Verriegelung


Kartonmaße und Brutto-Gewichte für Nähkopf

- 72x27x67 cm, 47 kg



GC 20606-	1	•	1.800	•	9	135x17/DPx17 160	36	•	8/13	20/3				M/H
	1D2	•	1.800	•	9	DPx17 160	36	•	8/13	20/3		•	•	M/H
		•	1.800	•	9	DPx17 160	36	•	8/13	20/3	•			M/H
	D2	•	1.800	•	9	DPx17 160	36	•	8/13	20/3	•	•	•	M/H

Specifications can differ depending on model.
Angaben können je nach Ausführung abweichen.



XI'AN TYPICAL EUROPE GmbH

Hertelsbrunnenring 9
D-67657 Kaiserslautern
Tel.: +49 (0)631 316019-0
Fax: +49 (0)631 316019-11

E-mail: sales@typical-europe.com
www.typical-europe.com