GC6180

HIGH-SPEED LOCKSTITCH SEWING MACHINE WITH DROP FEED

DOPPELSTEPPSTICH-SCHNELLNÄHER MIT UNTERTRANSPORT

TYPICAL

GC6180

HIGH-SPEED LOCKSTITCH SEWING MACHINE WITH DROP FEED

DOPPELSTEPPSTICH-SCHNELLNÄHER MIT UNTERTRANSPORT

Technical Data

- Stitch type 301
- Max. sewing speed 5,000 spm. (**GC6180ME3**)
- Max. stitch length 7 mm (**GC6180HE3, GC6180BE3**)
- Max. fabric clearance 13 mm with knee lever
- Balance wheel 70 mm eff. Dia

Clearance under the arm

- 260x130 mm

Automatic oil pump lubrication system

Models

- **GC6180ME3**
  Standard fast seamer for light to medium materials:
  Standard hook size; With automatic thread cutter,
  thread wiper and automatic back tacking
- **GC6180HE3**
  Standard fast seamer for medium to heavy materials:
  Standard hook size; With automatic thread cutter,
  thread wiper and automatic back tacking
- **GC6180BE3**
  Standard fast seamer for heavy materials:
  Large hook size; With automatic thread cutter,
  thread wiper and automatic back tacking

Carton dimensions and gross weights for sewing head

- 66x32x47 cm, 42 kg

Technische Daten

- Stichtyp 301
- Max. Nähgeschwindigkeit 5.000 Stiche/Min. (**GC6180ME3**)
- Max. Stichlänge 7 mm (**GC6180HE3, GC6180BE3**)
- Max. Durchgangsraum unter dem Nähfuß 13 mm
- Handraddurchmesser effektiv 70 mm

Durchgangsraum im Nähmaschinenarm

- 260x130 mm

Automatisches Druckumlauf-Schmiersystem

Ausführungen

- **GC6180ME3** | Standard-Schnellnäher für dünne bis mittlere Faden- und Materialstärken: Standard-Greifergröße; mit automatischem Fadenabschneider, Fadenwischer und automatischer Verriegelungseinrichtung
- **GC6180HE3** | Standard-Schnellnäher für mittlere bis schwere Faden- und Materialstärken: Standard-Greifergröße; mit automatischem Fadenabschneider , Fadenwischer und automatischer Verriegelungseinrichtung
- **GC6180BE3** | Standard-Schnellnäher für schwere Faden- und Materialstärken: Großer Greifer; mit automatischem Fadenabschneider, Fadenwischer und automatischer Verriegelungseinrichtung

Kartonmaße und Brutto-Gewichte für Nähkopf

- 66x32x47 cm, 42 kg

		301	MAX			System									LMH
6180 -	ME3	•	5,000	•	4.0	134/DPx5 70-110	31.8	6/13	•		•	•	•	○	L/M
	HE3	•	3,500	•	7.0	134/DPx5 100-160	35	6/13	•		•	•	•	○	M/H
	BE3	•	3,500	•	7.0	134/DPx5 100-160	35	6/13		•	•	•	•	○	H

○ **Options / Optionen**:
Automatic presser foot lifter / Automatische Nähfüßlüftung

Specifications can differ depending on model.
Angaben können je nach Ausführung abweichen.

Certificate of the international ISO9001 | Certificate of the ISO14001 | Certificate of the international CE | Certificate for Ecolabelling Product | Certificate for Energy Conservation Product

XI´AN TYPICAL EUROPE GmbH
Hertelsbrunnenring 9
D-67657 Kaiserslautern
Tel.: +49 (0)631 316019-0
Fax: +49 (0)631 316019-11

E-mail: sales@typical-europe.com
www.typical-europe.com

GC6180 – en/de – 05-2011